

OUTLAST. OUTPERFORM. OUTDELIVER.

QUICK QUOTE DATA ENTRY FORM

Please fill out as much as you can to ensure the most accurate quote possible.

Job Name:			Phone:			
Company Name:			Email:			
Contact Name:			Required On-Site Date:			
3-D Solid File: □Yes	□No					
Product Density: □Rigid □Flex	kible					
PRODUCT OPERATING ENVIRONMENT:						
Room Temperature: Product Temperature:						
Will product be in accumulation: □Yes □No						
Estimated % of conveyor to be filled: %						
	CONVEY	OR SPECIFIC	ATIONS:			
Frame Material Type: □Stainless □Aluminum □Powder Coated Steel						
Color If Painted: □Blue □Antique White □Silver □Charcoal Grey □Non-Standard						
Chain Series: Chain Width: Chain Style: Chain Color:						
Rod Type: □Coated Stainless □Coated Mild Steel □Uncoated Stainless						
Fill in Product Specifications Below:						
Product material in contact with conveyor:						
Product Name	Length	Width	Height	Weight	Rate (ppm)	
1.						
2.						
3.						
Cleanout Holes: □Yes □No						
Wearstrip Material: □Spanlon □	∃Mild Steel □	Stainless □Spar	nlon w/ Wood E	3ends		
Drive Type: □Pull □Push □Intermediate						
Wash Down: □Yes □No						

Idler On: □Standard □Low Profile					
Idler Off: □Standard □Low Profile					
Transfer On Type: □Gravity □Powered Roller □MicroSpan □None					
Transfer Off Type: □Gravity □Powered Roller □MicroSpan □None					
Bracket Type: □Fixed □Adjustable					
Guide Rails: □Round □1.25T □2.25T □None					
Side Walls: □Yes □No Side Wall Material: □Stainless □UHMW □Lexan					
Height of Wall above TOC:					
Fixed End Stop: □Yes □No					
SUPPORT STRUCTURES:					
Type: □Stainless Tubing □Painted Steel Tubing □Aluminum C Channel □None □Other					
Foot Option: ☐Bolted to Floor ☐Padded ☐Ceiling Mounted ☐Casters ☐NGI ☐Other					
Elevation:InfeedDischarge					
Drip Tray : □None □Vinyl Underguarding □Stainless □Painted □Lexan					
Metal Detector: □Yes □No Metal Detector Style:					
TRANSMISSION SPECIFICATIONS:					
Gear motor: □Yes □No					
Speed (Feet per Minute)					
Variable Frequency Drive: □Yes □No Variable Frequency Drive Brand:					
Variable Speed Range:					
Voltage: □110vAC □230vAC □460vAC □Other					
Gearbox Type: □Hollow Shaft □Remote Mount w/Chain & Sprocket					
Gear motor Brand: □SEW Eurodrive □Other					
Motor Starts/Stops per hour:					
Hours per Day Operation:					
ENVIRONMENTAL CONDITIONS:					
ENVIRONMENTAL CONDITIONS: Clean Room: □Yes □No					
Clean Room: □Yes □No					
Clean Room: □Yes □No Are Contaminants Present: □Yes □No □Unsure					